

LC540E

ENHANCED LOW VOLUME DESKTOP EMBOSSING SYSTEM

The Logika LC540E is a highly reliable embosser and an enhanced version of the LC450 / LC520 / LC540 systems.

Logika continue their policy of integrating the very latest technology into the LC540E, combining a robust and highly reliable system with that same great Logika build quality and functionality.

With in excess of 5000 systems installed worldwide, these systems have displayed a great longevity of use.

FEATURES

- desktop embosser
- superbly engineered
- top quality components and construction

AVAILABLE FUNCTIONS

- HiCo/LoCo magnetic encoding (ISO 7811)
- Embossing according to ISO standards, up to 11 lines
- Tipping
- Read back functions allows the LC540E to work with other systems e.g. the Logika TP950
- Optional mobile infiller for either front / rear indent
- Optional smart card module
- Additional dies available

TECHNICAL SPECIFICATION

- Front manual feed as standard
- Optional auto feeder: 100 cards
- Magnetic encoding 300/2750 Oersted ISO7811
- IC card initialisation: ISO 7816 standard
- PC controlled under Windows
- Standard embossing characters: 26 character English alphabet, 6 symbols standard Gothic, 10 number standard Gothic, 10 OCR 7B
- 6 additional positions for customised dies
- 8mm aluminium alloy plate chassis
- Optional 108 character drum

SYSTEM SPEED

- Up to 250 ISO CR80 cph

CARD SPECIFICATIONS

- Card ISO standard laminated CR80
- Material: PVC, ABS, PET
- Dimensions: ISO 7810
- Thickness: 0.76 mm

SOFTWARE

- Operating system: Windows XP
- Included application software: Badge



HOST CONNECTIONS

RS-232 serial port

POWER SUPPLY

220 V / 50 Hz or 110 V / 60 Hz

Single phase

DIMENSIONS AND WEIGHT

Dimensions 520 x 580 x 190 mm

Weight 40kg

ENVIRONMENTAL CONDITIONS

Operating Temperature: 14 – 27°C

Humidity: 20% - 85% non-condensing

LOGIKA

A LOGITONG COMPANY

Logika Technology Srl
Via de Vizzi 77
20092 Cinisello Balsamo
Milano
Italy
Tel ++39(0)26123477
Fax ++39(0)26659422
www.logika-italy.com