

LC900

MID-RANGE MODULAR MULTI-FUNCTION CARD PERSO SYSTEM

Logika LC900 recognises the market's growing demand for a mid-range, multi-function, high reliability, centralized card issuance system. The LC900 is ideal for EMV cards, IC cards and all standard cards.

FEATURES

- Mid-range desktop thermal printer
- Modular approach to protect the customer's investment and to grow with the customers applications and volumes
- Multi-task technology: each modules works simultaneously
- Superbly engineered for heavy duty
- Top quality components and construction

AVAILABLE FUNCTIONS

- HiCo/LoCo magnetic encoding (ISO 7811)
- Contact & contactless card initialization
- Dye sublimation thermal mono printing
- Dye sublimation colour printing
- Standard embossing
- Front or rear infill embossing
- Tipping
- 6 or 10 stations Contact IC card initialization
- 2 or 6 stations contactless IC card initialization

TECHNICAL SPECIFICATION

- Auto feeder: 350 cards
- 3-in-1 Motor driven encoder (hi/lo-co magnetic encoding, IC and RFID initialization)
- Magnetic encoding 300/2750 Oersted ISO7811
- IC card initialisation: ISO 7816
- RFID (Mifare B)
- Print area 81 x 51 mm
- Automatic out stacker: 300 cards
- Automatic reject hopper: 50 cards

SYSTEM SPEED

- IC credit card, up to 600 cph
- IC debit card, up to 1200 cph

CARD SPECIFICATIONS

- Card ISO standard laminated CR80
- Dimensions: ISO 7810
- Thickness from 0.6mm to 0.83mm

SOFTWARE

- Operating system: Windows XP, Vista, Win7
- Free application software --- Badge
- EMV compliant
- PBOC V2.0 compliant



HOST CONNECTIONS

USB

POWER SUPPLY

220 V / 50 Hz or 110 V / 60 Hz
Single phase

DIMENSIONS AND WEIGHT

Dimensions 116~180cm (L) x 58cm
(W) x 70 cm (H)
Weight 55kg up

ENVIRONMENTAL CONDITIONS

Operating Temperature: 14 – 27°C
Humidity: 20% - 85% non-condensing

Logika Technology Srl
Via C. Cattaneo 16/18
20035 Muggiò
Milano
Italy

Tel 0039 (0) 39 971 2506
Fax 0039 (0) 39 597 0291
www.logika-italy.com

LOGIKA
A LOGITONG COMPANY